Air Filter/AF20-A to AF40-06-A Made to Order

Please contact SMC for detailed dimensions, specifications and lead times.



AF30 to 40-06-A

В

AC-A

AF□-A AR-A

AL-A

AW-A

AC-B

AF-A

AF - A

AR:

AL-A

AW:

AW
AW
AV
AF


1 Long Bowl

Drain capacity is greater than that of standard models.

Applicable Model/Drain Capacity

Model	AF20-A	AF30-A	AF40-A	AF40-06-A	
Port size	1/8, 1/4	1/4, 3/8	1/4, 3/8, 1/2	3/4	
Drain capacity (cm ³)	19	43	8	18	
B dimension (mm) Note)	108.6	137.1	167.2	169.2	

Note) For polycarbonate bowls. Please contact SMC for other bowl materials.



- Semi-standard: Select one each for a to d.
- Option/Semi-standard symbol: When more than one specification is required, indicate in alphanumeric order.
 Example) AF30-03B-2R-A-X64

Body size
0 30 40

AF20-A

m

				0			
	Syn		Symbol	Description	Body size		
					20	30	40
			Nil	Rc	•	•	•
2	Pip	oe thread type	N Note 1)	NPT	•	•	•
_			F Note 2)	G	•	•	•
			+				
			01	1/8	•	_	_
			02	1/4	•	•	•
3 Port size		Port size	03	3/8	_	•	•
			04	1/2		_	•
			06	3/4	_	·—	•
			+				
		Nil	Without mounting option	•	•	•	
		on (woarting)	B Note 3)	With bracket	•	•	•
			+				
Semi-standard		a Bowl Note 4)	Nil	Polycarbonate bowl	•	•	•
			2	Metal bowl	•	•	•
	a		6	Nylon bowl	•	•	•
			С	With bowl guard	•	Note 5)	Note 5)
			6C	With bowl guard (Nylon bowl)	•	Note 6)	Note 6)
	.	+					
	<u> </u>	b Drain port	Nil	With drain cock	•	•	•
	b		Note 7)	Drain guide 1/8	•	_	_
		Brain port		Drain guide 1/4		•	•
			W Note 8)	Drain cock with barb fitting (for ø6 x ø4 nylon tube)		•	•
		+					
	c	Flow direction	Nil R	Flow direction: Left to right	•	•	•
		The state of the s		Flow direction: Right to left			•
		+					
	d	d Pressure unit	Nil	Name plate and caution plate for bowl in imperial units: MPa	•	•	•
	"		Z Note 9)	Name plate and caution plate for bowl in imperial units: psi, °F	Note 10)	O Note 10)	O Note 10)

Note 1) Drain guide is NPT1/8 (applicable to the AF20-A) and NPT1/4 (applicable to the AF30-A to AF40-06-A).

Note 2) Drain guide is G1/8 (applicable to the AF20-A) and G1/4 (applicable to the AF30-A to AF40-06-A).

Note 3) A bracket is not assembled and supplied loose at the time of shipment. Including 2 mounting screws.

Note 4) Refer to Chemical data on page 433 for chemical resistance of the bowl.

Note 5) A bowl guard is provided as standard equipment (polycarbonate).

Note 6) A bowl guard is provided as standard equipment (nylon). Note 7) Without a valve function

Note 8) The combination of metal bowl: 2 is not available.

Note 9) For pipe thread type: NPT. This product is for overseas use only according to the new Measurement Law. (The SI unit type is provided for use in Japan.)

Note 10) O: For pipe thread type: NPT only

